


RWP II


Insulated Roof and Wall Panel

The versatility of the RWP II panel offers a multitude of design options. It can be utilized for roof or wall applications. The standard exterior skin is smooth but can be embossed if requested. The interior skin is roll-formed with our standard interior Mesa profile.



FEATURES AND BENEFITS

- The RWP II panel utilizes a through-fastened attachment.
- The standard exterior surface is 26-ga. Galvalume coated steel with silicone polyester or Kynar 500/Hylar 5000 coatings.
- IMPs allow for fast assembly times and easy installation, resulting in reduced construction labor costs and earlier business starts.



PRODUCT PARAMETERS

Panel Thicknesses:	1 1/2"	2"	2 1/2"	3"	4"	5"	6"
R-values:	11.5	15.3	19.2	23	30.8	38.5	46.1
Panel Lengths:	8' to 50' maximum						
Insulation Material:	Non-CFC foamed-in-place polyisocyanurate foam 2.2 to 2.5 pcf density						
Joint Configuration:	Overlapping with exposed fasteners						
Metal facings:	26-ga. Steel (22, 24-ga. available)						
Coatings:	Silicone Polyester, Kynar 500/Hylar 5000						
Accessories:	Fasteners, Sealants, Brake-formed Flashings, Standard and Custom Trim						



INSULATED PANEL SYSTEMS

www.insulated-panels.com

14031 West Hardy, Houston, TX 77060

Phone: 800.729.9324 Fax: 281.499.3363